

**NOT FOR RETAIL SALE.  
FOR USE IN THE MANUFACTURING PROCESS ONLY.**

Makes cleaning easier and quicker. Dries fast with no greasy or oily film. Saves valuable time. Use on such surfaces as metal, glass, rubber, most plastics (except polystyrene) and painted finishes. It is colorless, nonstaining, waxless and heat-stable - unaffected by temperature ranging from (-40°C to 204°C). It has unusually low surface tension properties.

Reduces friction and annoying squeaks in hinges, latches, springs, gears and other mechanisms. The high-silicone formula is excellent for use to prevent corrosion on metal, to reduce friction and wear, and quiet moving parts. Provides a water and weather-resistant barrier that protects surfaces from corrosion and wear. Virtually odorless and colorless when dry.

**USED BY:** Industrial plants, printing industry, garment and textile industry, packaging plants, molding and cutting operations, shipping and package handling operations, construction and maintenance crews.

**DIRECTIONS:**

Thoroughly clean metal surfaces to be treated. Use steel wool and wipe with a good cleaning solvent if necessary. Clean rubber surfaces with water and detergent. Dry before spraying. Avoid overspraying. Spray a light, thin film. Remove excess with a clean cloth. Renew when necessary.

**SILI LUBE DRY SILICONE LUBRICANT**

**DANGER:** Extremely flammable aerosol. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

**FIRST AID: IF SWALLOWED:** Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. **IF IN EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. Get medical attention if irritation develops and persists.

**CONTAINS (CAS No.):** Propane (74-98-6), Aliphatic Petroleum Solvent (64742-89-8), n-Heptane (142-82-5), Cyclohexane (110-82-7), Polydimethylsiloxane (63148-62-9), Toluene (108-88-3) and n-Hexane (110-54-3).

Distributed By:  
HARPER SUPPLY LLC  
7924 CAMP BOWIE WEST BLVD,  
FORT WORTH, TX 76116  
817-529-1091 Office • 817-529-1092 Fax



**CAUTION:** Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**KEEP OUT OF REACH OF CHILDREN**

**Not for sale or distribution in California.**

See Safety Data Sheet for complete safety information.

**CONTAINS NO OZONE DEPLETING CHEMICALS!**

**24 HOUR MEDICAL EMERGENCY: 1-800-535-5053**

MADE IN THE U.S.A.

Distributed by

**HARPER  
SUPPLY**

# HARPER SUPPLY

## Sili Lube Dry Silicone Lubricant

Dries Fast

Non-Staining

Safe on Most Plastics

Heavy-Duty

Multi-Purpose

Dry Film Stable from -40°F to +399°F

**DANGER:**

HARMFUL OR FATAL IF SWALLOWED.

EXTREMELY FLAMMABLE.

EYE, SKIN AND RESPIRATORY TRACT IRRITANT.

CONTENTS UNDER PRESSURE.

SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ / 312 g