



DESCRIPTION

GORILLA COAT instantly bonds with rust, stops its growth, transforms it into a non-rusting paintable surface, and prevents future rust formation.

GORILLA COAT rust converter provides an excellent primer coating for the application of quality oil-based paints. Surfaces protected with this primer and an oil-based paint system resists the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces.

Do not breathe vapours. Wear eye protection, protective clothing, protective gloves. Get medical advice/attention if you feel unwell.

Dispose of contents/container to comply with local/regional/national/international regulations.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

HARPER SUPPLY GORILLA COAT

A PAINT ON SOLUTION THAT CONVERTS RUST
TO AN INERT PROTECTIVE COATING

• NON-FUMING

WARNING

May cause damage to organs (liver) through
prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: ONE GALLON (128 FL. OZ.)

Distributed By:
**HARPER
SUPPLY**

7924 CAMP BOWIE WEST BLVD.
FORT WORTH, TX 76116
817-529-1091 Office • 817-529-1092 Fax

DIRECTIONS

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: Shake or stir well before using. **GORILLA COAT** is ready-to-use. Do not dilute. Apply this product using a brush or roller. Apply a second coat to ensure complete transformation of rusty surfaces.

COVERAGE: 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of cure time before the application of the finished paint coat.

For long-lasting protection of iron surfaces, the cured rust converter should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

IMPORTANT: Do NOT return unused material to original containers.

NFPA® RATINGS

Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Proprietary Polymer/Proprietary;
2-butoxyethanol/111-76-2; Tannic Acid/1401-55-4; Oxalic Acid/6153-56-6

Please recycle 