

This R.T.V. Silicone Caulk and Sealant is ideal for use wherever a strong permanently elastic weatherproof caulk, sealant or adhesive is needed. Designed to seal non-porous surfaces around ceramic tile, cultured marble, showers, tubs, sinks and plumbing fixtures. Ideal for caulking windows, doors, sills and ceiling cracks and crevices. Features excellent adhesion and high chemical resistance. Will not sag or shrink during severe temperature changes. Useful for sealing cracks in machinery, heating and ventilation duct work, plumbing fixtures, electrical connections and low pressure water and drain lines. Bonds nameplates, machinery flanges, glass, signs, electrical insulation etc. Offers unmatched performance under the most severe conditions. Remains flexible and will not shrink, crack, crumble or dry out.

NOTE: Paint will not adhere to cured material. Not recommended for continuous immersion in water or application to porous surfaces such as masonry.

#### DIRECTIONS:

Read Safety Data Sheet before using.

1. Surface must be clean, dry and free of oil, tar, dirt and dust for best adhesion.
2. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surfaces.
3. Starts to cure immediately, fully cures in 24 hours and reaches optimum strength in 7 days. This product meets the requirement of FDA Regulation 21 CFR 177.2600, when fully cured and washed.

#### RTV SILICONE AND CAULK CLEAR

**WARNING:** Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes skin irritation. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves. Wear eye/face protection. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

**FIRST AID: IF ON SKIN:** Wash off with soap and water. Get medical attention if irritation develops and persists. Take off contaminated clothing. Wash contaminated clothing before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.

**CONTAINS (CAS NO.):** Polydimethylsiloxane (70131-67-8), Silica, amorphous (7631-86-9), Distillates, Petroleum, Hydro-treated Middle (64742-46-7), Ethyltriacetoxysilane (17689-77-9), Methyltriacetoxysilane (4253-34-3) and Difluoroethane (propellant) (75-37-6).

Distributed By:

HARPER SUPPLY LLC  
7824 CAMP BOWIE, WEST BLVD  
FORT WORTH, TX 76116  
817-529-1091 OFFICE • 817-529-1092 FAX



After each use, leave a small bead of material, which will form a sealing "plug" for reuse. To use, gently pull "plug" and begin to use material. If plug breaks, leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.

# HARPER SUPPLY

## RTV Silicone and Caulk CLEAR

- Seals, Bonds, Insulates
- Flexible
- Easy to Use
- Waterproof • Weatherproof
- 100% RTV Silicone - Industrial Strength
- Flexible from -60°F to +500°F
- Caulks tubs, sinks, showers and plumbing fixtures
- Seals windows, doors, tile, marble, etc.
- Bonds almost any material

**WARNING:** CONTACT WITH UNCURED SEALANT CAUSES SKIN IRRITATION. OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER. The propellant is not expelled with the product. It remains in the container after use. Care must be taken in storage and handling to avoid release of the propellant. However it does not present a hazard during normal use according to label instructions. Use with adequate ventilation. Product releases acetic acid (vinegar-like odor) during curing. Contact lens wearers take appropriate precautions. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

SEE SAFETY DATA SHEET FOR COMPLETE SAFETY INFORMATION.

CONTAINS NO OZONE DEPLETING CHEMICALS!

24 HOUR MEDICAL EMERGENCY: 1-800-535-5053

MADE IN USA

Distributed by

**HARPER  
SUPPLY**



**WARNING:** CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. CONTENTS UNDER PRESSURE. OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER. SEE OTHER CAUTIONS ON BACK PANEL. KEEP OUT OF REACH OF CHILDREN.

**NET WT. 8 OZ (227 g)**